



SOLIS



SOLIS

Integrated Solar Lighting system

Model 130

- Quick, easy and secure installation
- Dimming options
- Automatic activation
- No power cable or wiring required
- Flexible programming according to your needs



SOLIS-130

Integrated solar lighting system

Technical Specifications

Fixture <small>*10 year limited warranty</small>	Signify Road Focus RFS-35W12LED (35 Watts)
System voltage	12 Volts
Lighting	R2S, R2M, R3S, R3M, Type IV (ASYM), Type V (SYMM)
Temperature	2700K, 3000K -4000-K
Solar Panel	130 Watts - Monocrystalline - High efficiency
Battery	12 V 1200 Wh AGM battery
Controller <small>*5 years limited warranty</small>	SOLIS օպօլօ 12V High Efficiency
Operating Temperature	-35°C ~65°C
Construction materials	Aluminum
Options	IS1: Solar Panel Cover, IS2: No Solar Panel Cover
Finish	Electrostatic powder coating
Available colors	Black, White, Bronze, Silver and custom colors
Total weight	100 lbs - Without the pole (solar head only)
Recommended installation height	Between 15 and 25 feet
Ingress Protection Code	IP65
Motion sensor	25' Radius
Programming	10 Programs / schedules available Remote control available
EPA	7.1 sq.ft. (Solar head), 0.52 sq.ft. (Luminaire)

Lights and batteries certified



Contact SOLIS for more information:

Montreal area : +1 514 716 4465

info@solis-energy.ca solis-energy.ca